

**Teflon® Advanced Protector**

Version 2.0

Revision Date 12/15/2010

Ref. 130000050492

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Teflon® Advanced Protector
MSDS Number : 130000050492

Product Use : Carpet protector

Manufacturer : DuPont
1007 Market Street
Wilmington, DE 19898

Product Information : 1-800-441-7515 (outside the U.S. 1-302-774-1000)
Medical Emergency : 1-800-441-3637 (outside the U.S. 1-302-774-1139)
Transport Emergency : CHEMTREC: 1-800-424-9300 (outside the U.S. 1-703-527-3887)

Other information : professional use

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

The hazards of this product are associated mainly with its processing. Inhalation of decomposition products in high concentration may cause shortness of breath (lung oedema). Inhalation of aerosol or fine spray mist may cause serious respiratory problems.

Potential Health Effects

Skin : May cause skin irritation. May cause: Discomfort, itching, redness, or swelling..

Eyes : May cause eye irritation. May cause: tearing, Redness, Discomfort.

Inhalation : Inhalation of decomposition products in high concentration may cause shortness of breath (lung oedema). Inhalation of aerosol or fine spray mist may cause serious respiratory problems.

Carcinogenicity

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.


Teflon® Advanced Protector

Version 2.0

Revision Date 12/15/2010

Ref. 130000050492

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Water	7732-18-5	76 - 92 %
2-Methylpentane-2,4-diol	107-41-5	3 - 7 %
Partially Fluorinated Condensation Polymer		1 - 5 %
Acrylic Copolymer		3 - 7 %
Partially Fluorinated Amphiphilic Condensation Polymer		1 - 5 %

SECTION 4. FIRST AID MEASURES

- Skin contact : Wash off immediately with soap and plenty of water. Wash contaminated clothing before re-use.
- Eye contact : Rinse immediately with plenty of water for at least 15 minutes. Seek medical advice.
- Inhalation : Move to fresh air. Oxygen or artificial respiration if needed. Symptoms may be delayed. Call a physician immediately.
- Ingestion : Call a physician or poison control centre immediately. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- General advice : When symptoms persist or in all cases of doubt seek medical advice.



Teflon® Advanced Protector

Version 2.0

Revision Date 12/15/2010

Ref. 130000050492

SECTION 5. FIRE-FIGHTING MEASURES

Flammable Properties

Flash point : > 93 °C (> 199 °F)

Thermal decomposition : > 200 °C (> 392 °F)

To avoid thermal decomposition, do not overheat.
Thermal decomposition can lead to release of irritating gases and vapours.

Fire and Explosion Hazard : The product itself does not burn. Hazardous decomposition products formed under fire conditions. Hazardous combustion products: Hydrogen fluoride Carbon dioxide (CO₂) Carbon monoxide Other hazardous decomposition products may be formed.

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Firefighting Instructions : Wear self contained breathing apparatus for fire fighting if necessary. Evacuate personnel to safe areas. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Safeguards (Personnel) : Evacuate personnel to safe areas. Use personal protective equipment. Ventilate the area.

Spill Cleanup : Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers.

Accidental Release Measures : Do not discharge to streams, ponds, lakes or sewers. Avoid subsoil penetration.



Teflon® Advanced Protector

Version 2.0

Revision Date 12/15/2010

Ref. 130000050492

SECTION 7. HANDLING AND STORAGE

- Handling (Personnel) : Avoid formation of respirable particles. Do not breathe vapor or mist. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Wash contaminated clothing before re-use.
- Handling (Physical Aspects) : To avoid thermal decomposition, do not overheat. Thermal decomposition can lead to release of irritating gases and vapours. Do not spray near open flame or heated surface.
- Storage : Keep tightly closed in a dry, cool and well-ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering controls : Use only in area provided with appropriate exhaust ventilation. Use an airless flow type of spray applicator. Keep spraying pressure below 60 psi.
- Personal protective equipment
 - Respiratory protection : In case of mist or aerosol exposure wear suitable personal respiratory protection.
 - Hand protection : Additional protection: Impervious gloves
 - Eye protection : Wear safety glasses or coverall chemical splash goggles.
 - Skin and body protection : Lightweight protective clothing

Exposure Guidelines

Exposure Limit Values

2-Methylpentane-2,4-diol
 TLV (ACGIH) 25 ppm TLV-C

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.



Teflon® Advanced Protector

Version 2.0

Revision Date 12/15/2010

Ref. 130000050492

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid
 Color : white
 Odor : slight, acrylic-like
 pH : 6 - 9.2
 Freezing point : ca. 0 °C (32 °F)
 Boiling point : ca. 100 °C (212 °F) at 760 mm Hg
 % Volatile : 83 - 95 %
 Specific Gravity : 1.02
 Water solubility : dispersible

SECTION 10. STABILITY AND REACTIVITY

Stability : Stable under normal conditions.
 Conditions to avoid : To avoid thermal decomposition, do not overheat.
 Hazardous decomposition products : Carbon dioxide , Carbon monoxide, Hydrogen fluoride
 Incompletely burned carbon products
 Other hazardous decomposition products may be formed.

SECTION 11. TOXICOLOGICAL INFORMATION

Teflon® Advanced Protector
 Further information : No data is available on the product itself.
 2-Methylpentane-2,4-diol
 Dermal LD50 : 7,880 mg/kg , rabbit
 Oral LD50 : 3,700 mg/kg , rat
 Oral : animals (unspecified species)
 Lethargy
 Hypoactivity
 Inhalation 8 h ALC : > 87 mg/l , rat

**Teflon® Advanced Protector**

Version 2.0

Revision Date 12/15/2010

Ref. 130000050492

- Skin irritation : animals (unspecified species)
irritant
- Eye irritation : animals (unspecified species)
irritant
- Skin sensitization : guinea pig
Did not cause sensitization on laboratory animals.
- Mutagenicity : Did not cause genetic damage in cultured bacterial cells.
Did not cause genetic damage in cultured mammalian cells.
- Reproductive toxicity : Animal testing showed no reproductive toxicity.
- Teratogenicity : Animal testing showed effects on embryo-fetal development at levels
equal to or above those causing maternal toxicity.

Partially Fluorinated Condensation Polymer

- Oral ALD : > 11,000 mg/kg , rat
- Skin irritation : slight irritation, rabbit
- Eye irritation : slight irritation, rabbit
- Skin sensitization : Did not cause sensitization on laboratory animals., mouse

Patch test on human volunteers using dried treated fabric did not
demonstrate sensitization properties.,
- Mutagenicity : Tests on bacterial or mammalian cell cultures did not show mutagenic
effects.
- Reproductive toxicity : Animal testing showed no reproductive toxicity.
- Teratogenicity : Animal testing showed no developmental toxicity.

Partially Fluorinated Amphiphilic Condensation Polymer

- Dermal LD50 : > 5,000 mg/kg , rat
- Oral LD50 : > 5,000 mg/kg , rat
- Inhalation 4 h ALC : 1.363 mg/l , rat



Teflon® Advanced Protector

Version 2.0

Revision Date 12/15/2010

Ref. 130000050492

- Skin irritation : No skin irritation, rabbit
- Eye irritation : slight irritation, rabbit
- Skin sensitization : Did not cause sensitization on laboratory animals., mouse
- Mutagenicity : Did not cause genetic damage in cultured bacterial cells.

SECTION 12. ECOLOGICAL INFORMATION

- Aquatic Toxicity
- 2-Methylpentane-2,4-diol
 - 96 h LC50 : Pimephales promelas (fathead minnow) 8,690 mg/l
 - 72 h EC50 : Scenedesmus capricornutum (fresh water algae) > 429 mg/l
- Partially Fluorinated Condensation Polymer
 - 96 h LC50 : Oncorhynchus mykiss (rainbow trout) > 100 mg/l
Information given is based on data obtained from similar product.
 - 72 h NOEC : Algae > 100 mg/l
Information given is based on data obtained from similar product.
 - 72 h LC50 : Algae > 100 mg/l
Information given is based on data obtained from similar product.
 - 48 h EC50 : Daphnia magna (Water flea) 4.3 mg/l
Information given is based on data obtained from similar product.
- Partially Fluorinated Amphiphilic Condensation Polymer
 - 48 h EC50 : Daphnia magna (Water flea) > 120 mg/l
Information given is based on data obtained from similar product.

SECTION 13. DISPOSAL CONSIDERATIONS

- Waste Disposal : In accordance with local and national regulations.



Teflon® Advanced Protector

Version 2.0

Revision Date 12/15/2010

Ref. 130000050492

SECTION 14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA Status : Listed.
This material contains one or more substances which are subject to a TSCA Section 5 Consent Order or Significant New Use Rule (SNUR). See 40 CFR 721.10146 for SNUR requirements.
This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D:

Partially Fluorinated Condensation Polymer
PMN number: P-07-87
Partially Fluorinated Amphiphilic Condensation Polymer
PMN Number: P-08-200
This material shall not be distributed to consumers for use in spray applications.
Contact your local DuPont sales or technical representative for more information.

SARA 313 Regulated Chemical(s) : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65 : Chemicals known to the State of California to cause cancer, birth defects or any other harm: none known

PA Right to Know Regulated Chemical(s) : Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more (0.01% for Special Hazardous Substances): 2-Methylpentane-2,4-diol

NJ Right to Know Regulated Chemical(s) : Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more (0.1% for substances



Teflon® Advanced Protector

Version 2.0

Revision Date 12/15/2010

Ref. 13000050492

identified as carcinogens, mutagens or teratogens): 2-Methylpentane-2,4-diol

SECTION 16. OTHER INFORMATION

HMIS

Health	:	1
Flammability	:	0
Reactivity/Physical hazard	:	0

Teflon®, and DuPont™ are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates. The DuPont Oval Logo is a registered trademark of E.I. du Pont de Nemours and Company.

Contact person : MSDS Coordinator, DuPont Chemicals and Fluoroproducts, Wilmington, DE 19898, (800) 441-7515

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.